



SYSTEM REQUIREMENTS LIST: FIREWALL, PROXY, & PC SETTINGS

Firewall or Proxy Settings:

- 1Link.fhlbny.com will reside within the FHLBNY networks of 206.28.71.0/24 and 12.0.19.0/24.
 - Ensure port 443 (HTTPS) is open outbound to 1Link ranges.

PC Settings:

- Browser – Windows Internet Explorer 6 or 7
 - The Web browser must be configured to accept cookies and must have Java, JavaScript and frames enabled.
 - Browser Settings:

▪ First-Party Cookies	Accept or Prompt
▪ Active Scripting	Enable or Prompt
▪ Scripting of Java Applets	Enable or Prompt
▪ Third-Party Cookies	Accept or Prompt
▪ Trusted Sites	https://1link.fhlbny.com https://adminservices2.managed.entrust.com
▪ Do not save encrypted pages to disk	Checked to perform downloads and exports and to view PDF reports in 1Link
 - Java Support:

▪ IE6 with XP:	Sun Java: 1.4.2_x, 1.5 Update 12+, 1.6 Update 3+;
▪ IE7 with XP:	Sun Java Plugin 1.4.2+/1.5.0_04+/1.6 Update 3+;
▪ IE7 with Vista(32bit):	Sun Java Plugin 1.6 Update 10+
 - Pop-Up Blocker:

▪ Permit Sites	https://1link.fhlbny.com https://adminservices2.managed.entrust.com
----------------	--
- Minimum screen resolution – 1024 x 768 pixels
- Active USB port
- Operating system
 - Windows XP - SP2 or later for transaction capabilities, plus these additional items:
 - Windows XP requires the Microsoft Update “Microsoft Base Smart Card Cryptographic Service Provider Package” to be installed (<http://support.microsoft.com/kb/909520>). Most PCs will use the x86 version.
 - Windows XP requires a hardware driver (<http://support.gemalto.com/?id=46>) for the smartcard reader.
 - Windows Vista - SP1 or later for transaction capabilities